

TEST DATA SHEET

Description: PM Patchcord

Part Number: PMJP-FA-FA-1550-1-5-5m

| Parameters | | Center Wavelength | IL | ER | RL |
|-------------------|--------------------|-------------------|----------------------|-------|-----|
| Unit | | nm | dB | dB | dB |
| Specification | | 1550 | ≤0.30 | ≥23 | ≥55 |
| Item | S/N | 1550 | | | |
| 1 | PMPC240316002 1 | | -0.06 | -25.6 | 60 |
| 2 | PMPC240316002 2 | | -0.09 | -26.5 | 61 |
| 3 | PMPC240316002 3 | | -0.11 | -25.5 | 62 |
| 4 | PMPC240316002 4 | | -0.17 | -25.7 | 61 |
| 5 | PMPC240316002 5 | | -0.13 | -28.3 | 61 |
| 6 | PMPC240316002 6 | | -0.16 | -27.8 | 62 |
| 7 | PMPC240316002 7 | | -0.19 | -25.9 | 63 |
| 8 | PMPC240316002 8 | | -0.25 | -25.6 | 62 |
| 9 | PMPC240316002 9 | | -0.18 | -27.6 | 63 |
| 10 | PMPC240316003 0 | -0.09 | -27.5 | 61 | |
| Alignment Type | | | Slow axis to the key | | |
| Connector Type | | | FC/ APCx2 | | |
| Fiber Type | | | PM1550 | | |
| Fiber Length(m) | | | 5.0 | | |
| Max.Optical Power | | | 500mW | | |
| Buffer Type | | | 3mm PVC Tube | | |

Package Dimensions:



Tested by: 007



Date: 2024-3-15